

# **A.B.33**



# ANTI-FOG TREATMENT LONG LASTING EFFECT 0% alcohol

# **DESCRIPTION**

**A.B. 33** leaves on treated surfaces a transparent anti-fog film.

**A.B. 33** reduces the phenomena of adhesion or condensation of steam or wet air on cold surfaces by facilitating their drainage and their evacuation.

**A.B. 33**, in recommended conditions of usage, do not modify the transparency and does not affect the general aspect of surfaces: glass, windows, mirrors ...

**A.B. 33** improves the visibility.

**A.B. 33** limits deposits of limestone and water spots on the treated surfaces

## TECHNICAL DATA:

Physical state: liquid

Density: 800 g/l +/- 20g/l Chemical reaction: Neutral

Color: colorless

## **INSTRUCTIONS OF USE:**

Ensure surface is clean and dry.

Spray a light mist of Anti-Fog Treatment.

Spread horizontally using a soft cloth.

Wait a few seconds.

Spray again a light mist of **A.B. 33** and spread vertically using a soft cloth.

Then, wipe off with a soft and dry cloth without pressure (avoid wiping off in circular motions)

**Ref. 139M - Spray 150ml** 

Shelf life: 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

