

# **BRIGHT TECK**



# CONCENTRATED TEAK BRIGHTENER STEP N°2

# **DESCRIPTION**

**BRIGHT TECK** has a very powerful penetrating action for the second stage in the restoration of a teak deck.

**BRIGHT TECK** should be used immediately after the teak cleaner **SUN TECK**.

**BRIGHT TECK** is a controlled acid-based product which uses a combination of active substances to restore teak decks to their original colour.

**BRIGHT TECK** does not affect in any way the caulking when rates of dilution and exposure times are respected.

**BRIGHT TECK** removes greyish stains cause by severe weather, salt water and pollution, restoring the teak to its natural colour.

## TECHNICAL DATA:

- Physical state : fluid Liquid - Density : 1055 g/l +/- 20 g/l.

pH pur: 2.10 approx. (acid)Colour: colourless

## **INSTRUCTIONS OF USE:**

**NEVER USE PUR.** 

- Dilute 1 litre of product for 3 to 5 litres of water depending on the level of staining.
- First of all, wet the teak and the hull.
- It is advised to do not work to direct sunlight in order to avoid black stains on gelcoat and paint.
- Apply the solution evenly with a soft brush.
- Leave for 10 to 15 minutes.
- Do not rub.
- Rinse abundantly with a water jet.

Coverage for 1 litre of product: 5 to 7 m<sup>2</sup>.

Ref. 639M - Bottle 1L Ref. 639M.5 - Bottle 5L Ref. 639M.10 - Bottle 10L Shelf life : 3 years Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

