

DESCRIPTION

CHALKEX is a powerful pickle containing corrosion inhibitors.

CHALKEX pickles perfectly the propellers, the shaft gears, the base plates and the hulls.

CHALKEX removes barnacles, zebra mussels, algae, scum lines quickly and easily.

CHALKEX is especially studied for a fast and effective pickle of propellers, propellers shaft and hulls. A simple rinsing with the water jet is enough for remove the deposits.

CHALKEX does not release any harmful vapor.

TECHNICAL DATA :

Physical state: Liquid Color: light red pH : strongly acidic. pH value : 0.1 – 0.3 Vapour pressure: 227 hPa at 21,1 °C Density: 1.113 +/- 0.01 Water solubility: Dilutable.

INSTRUCTIONS OF USE :

It is a product ready to use.

CHALKEX is best used at a minimum 15°C ambient temperature. Low temperature slows the action of the product.

Just spray on and let act a few minutes.

Then rinse with the water jet.

If it is necessary, renew the operation.

- * Working temperature +15°C to +30°C.
- * Close the container well after use.
- * Protect from frost.



Shelf Life : 3 years

Keep out of the reach of children. Reclose the packaging after each use. Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight. Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.



SAS MATT CHEM PRODUCT® FRENCH MANUFACTURE (92) Bagneux France Tel : + 33 (0)1 42 53 73 73 www.mattchem.fr - info@mattchem.fr November 2021