



COMBIFUEL



GUARD TREATMENT FOR DIESEL OIL WATER ABSORBER

DESCRIPTION

COMBIFUEL eliminates water in fuel oil.

COMBIFUEL dissolves mires on the tank bottom.

COMBIFUEL, product anti-corrosion, neutralizes SO₂ and SO₃. It prevents rust formation in fuel-oil pump, «water-separators», filters and injectors.

COMBIFUEL increases "Ketan" Number.

COMBIFUEL keeps motor clean.

COMBIFUEL fights salt effect and reduces widely scoria's formation.

COMBIFUEL protects valves and kills bad smells.

COMBIFUEL decreases freezing point of - 20° C and dissolves paraffin.

COMBIFUEL grants to do combustible economies.

COMBIFUEL contributes to pollution supervision and reimburse itself because it improves the combustion and increases the motor efficacy.

TECHNICAL DATA :

Physical state: fluid liquid.

pH: Not applicable.

Flash point: 63.00 ° C.

Density: 0.850 - 0.950

Water solubility: Insoluble.

Viscosity: $\nu < 7 \text{ mm}^2 / \text{s}$ (40 ° C)

INSTRUCTIONS OF USE :

After treating your fuel with **BACT FUEL**, add **COMBIFUEL** to your tanks, knowing that a quantity of 125 ml treats 500 litres of diesel. Do not pour in an empty tank. **BACT FUEL** and **COMBIFUEL** can be added at the same time into the tank.

Ref. 565MFL - Bottle 125 ml

Ref. 442M - Bottle 1 litre

Ref. 442M.5 - Bottle 5 litres

Shelf life : 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

MATT CHEM[®] MARINE

SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : + 33 (0)1 42 53 73 73
www.mattchem.fr - info@mattchem.fr
November 2021