



# CRAQUY



## FREEZING PICKLE FOR SHAFT GEARS, PROPELLERS, HULLS AND INFLATABLES

### DESCRIPTION

**CRAQUY** is powerful pickle which contains corrosion inhibitors.

**CRAQUY** pickles perfectly the propellers, the shaft gears, the base plates and the hulls.

**CRAQUY** also makes it possible to pickle the inflatables without any attack of PVC, hypalon or neoprene.

**CRAQUY**, as it is a freezing, does not make streaks. **CRAQUY** adheres perfectly to surface what avoids the loss of product.

**CRAQUY** removes barnacles, zebra mussels, algae easily.

A simple rinsing with the water jet is enough for remove the deposits.

**CRAQUY** does not release any harmful vapor.

### TECHNICAL DATA :

Physical state : Gel

Aspect : Viscous

Colour : Amber

Density : 1135g/l +/- 20 g/l

Chemical reaction : acid

### INSTRUCTIONS OF USE :

**CRAQUY** is best used at a minimum 15°C ambient temperature. Low temperature slows the action of the product.

Preferably do not work in sunlight to avoid evaporation of the gel.

Apply **CRAQUY** with a brush or a roller paint.

Let act 15 to 20 minutes.

Rinse with a water jet or a water compressor.

\* Working temperature +15°C to +30°C.

\* Clean tools with water.

\* Close the container well after use.

\* Protect from frost.

**Ref. 661M - Can of 500ML**

Shelf Life : 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to [servicetechnique@mattchem.fr](mailto:servicetechnique@mattchem.fr).

# MATT CHEM<sup>®</sup> MARINE

SAS MATT CHEM PRODUCT®  
FRENCH MANUFACTURE  
(92) Bagneux France  
Tel : + 33 (0)1 42 53 73 73  
[www.mattchem.fr](http://www.mattchem.fr) - [info@mattchem.fr](mailto:info@mattchem.fr)  
November 2021