

FLEXIKLINE



CONCENTRATED GLEANER FOR PVC TEAK DECKING SYSTEM

DESCRIPTION

FLEXIKLINE removes perfectly grease, oil and tar marks on PVC teak deck material.

FLEXIKLINE removes quickly vegetable pollution such as the algae and moss.

FLEXIKLINE is safe to use for gelcoat, paint, plastic and light alloys under the recommended conditions of use.

TECHNICAL DATA:

Physical state: Fluid liquid.

pH (aqueous solution) : at 5 % = 11,10

Boiling point/boiling range: Not specified.

Flash point interval: Not relevant.

Vapour pressure (50°C): Not relevant.

Density: 1.045 - 1.055

Water solubility: Dilutable.

INSTRUCTIONS OF USE:

FLEXIKLINE is a concentrated cleaner to dilute.

- For the daily care, the dilution is 150 ml for 5 litres of water.
- For the cleaning of very dirty PVC teak deck (at the exit from shipyard or after a conveying), the dilution is 500 ml for 5 litres of water.

Rub the hull with a soft brush or sponge.

Rinse.

Ref. 336M - Bottle 1L Ref. 336M.5 - Bottle 5L Shelf life : 3 years Keep out of the reach of children. Reclose the packaging after each use. Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight. Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

