



GALVANY

GALVANIZATION ZINC SPRAY

DESCRIPTION

GALVANY contains filing metal ensuring an exceptional anti-corrosion protection.

GALVANY has a very good adherence on oxidized, rusted or chrome surfaces.

GALVANY brings back the brightness at the heated surfaces.

GALVANY ensures a longtime protection against corrosion.

TECHNICAL DATA :

- Physical state : Viscous Liquid.
- Density : 970 g/l +/- 20 g/l.
- Chemical reaction : Neutral.
- Flash Point : < 21 °C AFNOR closed cup.
- Odour : Characteristic of solvent.
- Colour : Silver

INSTRUCTIONS OF USE :

Spray **GALVANY** on a clean and dry surface at 20 to 25 cm from the surface.

Wait a few minutes and apply a second coat.

Time of drying: 1 hour.

Advice :

Frequently shake the aerosol in the event of long pulverization.

At the end of use, drain the head's aerosol in order to avoid the obstruction of the valve of the pushbutton.

Ref. 597M - Aerosol 500ML

Shelf life : 18 months

Keep out of the reach of children. Reclose the packaging after each use.
Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.
Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

MATT CHEM[®]
MARINE

SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : + 33 (0)1 42 53 73 73
www.mattchem.fr - info@mattchem.fr
November 2021