

H.P.C



COLOURLESS DOUBLE-SIDED TAPE INSTANT BONDING

DESCRIPTION

H.P.C is a colourless double-sided tape for instant and permanent bonding.

H.P.C is a proven alternative to screws, rivets, welds and other forms of mechanical fasteners.

H.P.C can be applied on any kind of surface such as glass, plexiglas, plastic, gelcoat, metal

TECHNICAL DATA :

- * 180° peel adhesion on stainless steel : 2000g/cm
- * Tensile strenght : 6,7 kg/cm²
- * Service temperature resistance : -40° à 120°C
- * Solvent resistance : Good
- * U.V. resistance: Excellent
- * Moisture resistance : Excellent

INSTRUCTIONS OF USE :

The application's temperature is between +15°C et +30°C.

H.P.C must be applied on a cleaned and dry surface free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level.

The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Ref. 282M
Roll 10 M

Shelf Life : 2 years

Keep out of the reach of children. Reclose the packaging after each use.
Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.
Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattechm.fr.

MATT CHEM[®]
MARINE

SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : + 33 (0)1 42 53 73 73
www.mattechm.fr - info@mattechm.fr
November 2021