

## .B.S



# WATERPROOFING FOR FABRIC BOAT COVERS AND FABRIC BIMINI TOPS

#### DESCRIPTION

**I.B.S** is a waterproofing for synthetic and cotton fabrics.

**I.B.S** keeps the fabric waterproof and breathable.

- I.B.S prevents rot and mildew stains.
- **I.B.S** answers caracteristic following:
- does not contain silicone.
- insoluble in water.
- does not change color of fabric.

#### **TECHNICAL DATA :**

- Physical state : Fluid liquid.
- pH : Not relevant.
- Flash Point : 40.00 °C.
- Density : 0.780 0.800

### INSTRUCTIONS OF USE :

**I.B.S** is always used pure. Apply it on a cleaned and dry surface.

- Spray on finely and regularly in cross let dry at 20cm for the fabric.
- Coverage : 500ML of **I.B.S** treat  $+/-4m^2$ .
- Time of drying at 20°C : 5 to 6 hours .
- Do not apply to wet surfaces and into direct sunlight.
- Apply at an ambient temperature >+10°C and <+30°C ADVICE :
- In case of fragile fabric, Always carry out a test prior to use.

Avoid any projection on polished or glazed surfaces. In the event of projection, clean immediately with white spirit and rinse.

Ref. 642MS05 Spray 500ml Ref. 642M - Bottle 1 litre Shelf life : 18 months

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight. Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.



SAS MATT CHEM PRODUCT® FRENCH MANUFACTURE (92) Bagneux France Tel : + 33 (0)1 42 53 73 73 www.mattchem.fr - info@mattchem.fr November 2021

- Water solubility : Insoluble.
- Viscosity: v < 7 mm2/s (40°C)