



MATTCO

TEAK SEALER SLIGHTLY AMBER



DESCRIPTION

MATTCO is a sealer for teak slightly amber.

MATTCO contains resins and synthetic polymers.

MATTCO prevents mildew and delays the biological degradation of wood by micro-organisms.

MATTCO does not scale, does not yellow and does not crack.

MATTCO contains UV protection.

MATTCO nourishes teak and brings back the hot tone of teak.

TECHNICAL DATA :

Physical state : Liquid.

Density : 815 g/l +/- 10 g/l.

Chemical Reaction : Neutral.

Flash Point : 42 °C. +/- 2°C. AFNOR

Color : Slightly amber

Odor : Solvent

INSTRUCTIONS OF USE :

MATTCO is used pur.

Apply to the paint brush on a cleaned, dusted and perfectly dry teak.

Well shake the bottle before use.

Apply a 1st uniform and regular thin coat in the direction of the wood at an ambient temperature of minimum 15°C.

Wait for a few moments and apply a 2nd coat always in the direction of the wood.

Under normal circumstances the teak should be dry to the touch in 30 minutes approximately.

The maximal protection is effective after 12 hours at a room temperature of 20°C

(Cool and damp weather slows down the time of drying)

Indicative coverage : +/- 10 m² per litre

Ref. 327M - Can 1L
Ref. 327M.4 - Can 4L
Shelf life : 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

MATT CHEM[®] MARINE

SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : + 33 (0)1 42 53 73 73
www.mattchem.fr - info@mattchem.fr
November 2021