



MATT DEGRIP'

PENETRATING OIL FOR MECHANICAL COMPONENTS

DESCRIPTION

M. 4605 is a cleaner especially formulated to provide a complete cleaning of the boat.

Its grease-removing function and hydrosolubility of the greasy deposits make it possible to clean perfectly the gelcoat and the paint without any risk of deterioration.

M. 4605 forms a compact foam, which clings perfectly on the vertical surfaces of hull. It is necessary to let act the foam which dissolves grease and hydrocarbons.

M.4605, once diluted, can be applied manually to the sponge or the brush.

TECHNICAL DATA :

Physical state : Liquid

Density : 870 g/l +/- 20 g/l

Chemical reaction : neutral

Flash point : 53 °C AFNOR closed cup

Flammability : Flash point > to 21° C and < than 55 °C, Class A2.

Superficial tension : 30 dynes/cm.

INSTRUCTIONS OF USE :

- Must be diluted before use:
- Advise dilution : 4 to 5 cups of shampoo for 5 litres of water.
- Wet the surface.
- Apply the solution with a brush or a sponge.
- We advise you to apply this foaming cleaner with a gun foam.
- Let act the foam in surfaces
- Scrub.
- Rinse.

Ref. 197M - Aerosol 150ml

Shelf Life : 3 years

Keep out of the reach of children. Reclose the packaging after each use.
Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.
Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

MATT CHEM[®]
MARINE

SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : + 33 (0)1 42 53 73 73
www.mattchem.fr - info@mattchem.fr
November 2021