

## **MATT ZIP**



# LUBRICANT GEL SILICONE BASED FOR SLIDES AND ZIPS

### **DESCRIPTION**

MATT ZIP is a silicone translucent synthetic grease, chemically inert.

MATT ZIP is a Grease NLGI 3.

MATT ZIP is effective at very low temperature and protects effectively against moisture.

**MATT ZIP** is water repellant and performs even when exposed to water and maintains its protective as well as lubricating properties.

MATT ZIP can be applied on all dry surfaces of glass, plastic, metal, rubber.

MATT ZIP is a perfect anti-adhesive.

#### TECHNICAL DATA:

Color: Colorless
Density at 20°C (Standard NF T 06 007): 0.950 - 1.100

Penetration at 25°C : 220 - 250 (Standard NFT 60132)

Appearance: Gel

Thermal conductivity (W/M.K): +/- 0.10

Dielectric constant (Standard NF C 26 230) : 2.7

Operating temperature range: -40°C / +250 °C

#### **INSTRUCTIONS OF USE:**

Apply MATT ZIP onto a clean, dust-free and perfectly dry surface.

If necessary, spread with a small brush.

**Ref. 201M - Tube 10 grs**Shelf life: 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

