

META MATT

WHITE EPOXY STICK



DESCRIPTION

META MATT is a paste containing epoxy resin free from solvent that is easy to use.

META MATT adheres easily on the majority of materials.

META MATT can be mixed in water.

META MATT becomes hard like steel even in the presence of water.

META MATT can be machined, tapped, threaded, sawn, sandpapered, milled and painted.

META MATT repairs all metals, plastics, wood and fibreglass.

META MATT has an excellent strength to the thermal shock, water, condensation, the vibrations, the corrosive and wet atmospheres....

TECHNICAL DATA :

Working time : 15 min. at 20°C

Hardness shore D : 65

Resistance in the cutting on steel: 6,2 mpa

Limits of temperatures:

* 120°C continuously

* 150°C at intervals

Electric Resistance: 30000 megohms

INSTRUCTIONS OF USE :

First of all, clean the surface to be treated.

Return rough the part having to receive **META MATT**.

Cut a portion of paste, mix it and knead it until obtaining a homogeneous paste of uniform colour during approximately 1 minute.

Apply the mixture with a knife or a spatula.

Time of drying approximate at ambient temperature = 1h30 to 3h.

At 40°C, dry in 40 minutes.

Ref. 529ML - Stick of 63 grs
Ref. 529M - Stick of 122 grs

Shelf life : 18 months

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.