



M.F.1



GASOIL / DIESEL TREATMENT

- BEST COMBUSTION
- LUBRICATION OF INJECTORS

DESCRIPTION

M.F.1 allows perfect diesel combustion which gives more power to the engine and better accelerations.

M.F.1 increases the cetane index and thus reduces the consumption of diesel in a very significant way.

M.F.1 dissolves the paraffin and disperses the impurities contained in the gas oil.

M.F.1 reduces pollution due to fuel combustion.

M.F.1 cleans and lubricates the injectors, valves, injection pump and compression chamber.

M.F.1, by improving combustion, strongly decreases smoke emissions.

M.F.1 facilitates cold start.

TECHNICAL DATA :

Density: 860g/l +/- 20g/l

Chemical reaction: neutral.

Aspect: liquid

Smell: hydrocarbon characteristic

Flash point: 63°C, afnor closed cut

Color: brown

INSTRUCTIONS OF USE :

Pour a dose of 125 ml of **M.F.1** per 250 litres of diesel.

Note: Never pour into an empty tank.

Ref. 562MFL - Bottle 125ml

Ref. 562M - Bottle 1 litre

Ref. 562M.5 - Bottle 5 litres

Shelf life : 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

MATT CHEM[®] MARINE

SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : + 33 (0)1 42 53 73 73
www.mattchem.fr - info@mattchem.fr
November 2021