





## EFFERVESCENT TABLET TREATMENT FOR HOLDING TANKS

## **DESCRIPTION**

SIMPLY TANK a rapidly dissolving treatment tablet that remains highly effective even in areas with hard water.

SIMPLY TANK is rich in active ingredients. The formulation is based on a synergised combination of an association of non-genetically modified class 1 revivifiable bacteria and enzymes, surface-active agents reducing surface tension and biological mineral activators.

SIMPLY TANK liquefies rapidly all organic waste products (Fatty matter, fecal matter, urea).

SIMPLY TANK also contains enzymes active on cellulose fibers and papers, pure tissue paper, cellulose wadding.

SIMPLY TANK thanks to its bio-cleaning enzymatic functions, deteriorates, digests the deposits made up of cellulose derivatives and fecal organic matter.

SIMPLY TANK stops unpleasant odours caused by the fermentation of certain types of waste products.

SIMPLY TANK has a pleasant smell red fruits.

## TECHNICALA DATA

- Physical state: 5-gramme compact tablet

- Colour: Clear blue green

- Scent: Red fruits

- Active ingredient content: 100%

- Chemical reaction/pH: 5,50 at 0,4 %

## INSTRUCTIONS OF USE

Put 4 tablets for a 100-litre tank. Add 1 litre of water. The tablet dissolves quickly on contact with water.

Refills to be renewed according to the frequency of use, the periodicity of emptying the tank, the appearance of solid deposits, piles of toilet paper sheets, bad smells and ambient temperature

(An increase of the ambient temperature may increase the proliferation of putrid odors, so increase the dose of use according to).

NB: Generally, depending on intensity and ambient temperature, allows a use of 6 days minimum to 15 days maximum before renewing.

IMPORTANT: Always securely close the lid immediately after removing tablets from the box. Keep dry.

Ref. 354M.20 - 20 doses de 5 grs GENCOD : 3760164172469

UFI: JUR3-50K1-P005-F1MY Shelf life: 3 YEARS Keep out of the reach of children. Always reseal the packaging after taking a tablet.

Always carry out a test on the surface to be treated beforehand to determine compatibility and the appropriate contact time. Please refer to the available safety data sheet (SDS) and to the texts on the packaging, which comply with current legislation.

The content of this documentation does not in any way engage our responsibility as to its application to each particular case. This data sheet may be revised at any time for reasons relating to legislation, the availability of components or new experience. The latest version of this data sheet, which is the only valid one, will be sent to you on request.



