

STOPO



SATURATOR FOR TEAK WATER-REPELLING AND COLOURLESS

DESCRIPTION

STOPO is a new generation of water-repelling saturator for the treatment of teak and other exotic woods. It is based on an aqueous formula, and does not contain any organic solvents.

STOPO is a colourless water-repellant which reduces significantly the ability of wood to absorb water.

STOPO can be used for both interior and exterior woodwork.

STOPO allows a subsequent application of solvent or aqueous-based paint or varnish.

STOPO comes ready to use and can be applied with a brush on the surface to be treated.

The product starts to work 30 minutes after being applied. According to the climate conditions, the full water-repelling effect is reached 48 hours after being applied.

TECHNICAL DATA:

Physical state : Liquid Density : 8.51

Colour : White Notes : pounds/gallon

pH: 8 to 10.5 Specific gravity: 1.02 g/mL Boiling temperature: (212°F) to (369°F) Solubility in water: Miscible

Viscosity #1 : < 100 cps

INSTRUCTIONS OF USE:

STOPO is ready to use.

Well shake the bottle before use.

Apply with a paint-brush on a clean and dry surface at a temperature > 15°C.

An even better protection can be attained by applying several coats.

It is important to wait 30 minutes between coats. The increase in protection diminishes after 2 coats.

Each coat uses about 1 litre per 15m².

Ref. 918M - Bottle 1 litre Ref. 918M.5 - Bottle 5 litres

Shelf Life: 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

