



U.V.P.S

SOLAR PANELS GUARD



DESCRIPTION

U.V.P.S is a multi-functional fluid based on a copolymer organo-mineral liquid providing preventative treatment of solar panels.

U.V.P.S leaves a durable ultra thin film, invisible, with very high level characteristics of “unwetability” and adherence resistance.

U.V.P.S prevents the formation of a water film.

U.V.P.S is effective for about 3 months.

TECHNICAL DATA :

- Physical state : Fluid liquid.
- Boiling point/boiling range : > 35°C
- Flash point interval : PE < 23°C
- Vapour pressure (50°C) : Not relevant.
- Density : 795 g/l +/- 20g/l.

INSTRUCTIONS OF USE :

U.V.P.S is applied on completely clean, dry surfaces.

Apply **U.V.P.S** on the surface to be treated with a clean rag.

Spread uniformly on the surface in horizontal lines.

Leave to dry 1 to 3 minutes.

Apply a second coat in vertical lines. Leave to dry again. Wipe the surface with a damp cloth or sprinkle with water.

Then wipe with a clean, dry cloth until the surface becomes clear again.

*Do not apply on hot surface and into direct sunlight.

*Do not apply the product with a squeegee.

*Do not apply if it rains.

*Application temperature between + 10°C and + 20°C.

Ref. 119M - Bottle 150ml

Shelf life : 3 years

Keep out of the reach of children. Reclose the packaging after each use.

Exposure to sun and extreme temperatures should be avoided. Keep out of direct sunlight.

Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Before use, read the label safety section for Health and Safety Information or request the safety data sheet to servicetechnique@mattchem.fr.

MATT CHEM[®] MARINE

SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : + 33 (0)1 42 53 73 73
www.mattchem.fr - info@mattchem.fr
November 2021